

SafeMask® Fit+Pro

Technical Data Sheet

M62110V

FFP2 NR respiratory protective mask – with valve Category III Personal Protective Equipment

FEATURES & BENEFITS

- Folded 3-panel design adapts to various face shapes and sizes.
- Sealing foams on both the upper and lower panels ensure a perfect seal while providing unmatched comfort for the wearer.
- Easy to put on and adjust thanks to sliding elastic straps and a tightening ring.
- The exhalation valve effectively expels heat and humidity, reducing the risk of fogging on the wearer's glasses.
- Its individual packaging helps control the risk of contamination.

Recommended uses

- Protection against viruses and bacteria
- Environments with moderate level of fine dust (construction, drilling/sanding, agriculture)
- Pharmaceutical industry and laboratories
- Work in moderately hazardous environments (metallurgy, woodworking, textiles).



Product name: SafeMask® Fit+Pro
Product type: Single use, non sterile
Fasteners: Sliding transverse elastics
Composition: Nose strip: Aluminium

Foams: PVC

Valve: Polypropylene + silicone Elastics: Spandex + polyester

Inner & outer layers: Spunbond polypropylene

Filter: Meltblown polypropylene

Origin: China

ltem	FFP Class	Valve Yes/no	Elastic Color	Unit weight (+/- 10%)	Qty / box
M62110V	FFP2 NR	Yes	Blue	18 g	12



FFP2 NR respiratory protective mask - with valve **Category III Personal Protective Equipment**

CERTIFICATIONS & STANDARDS

- In accordance with requirements of Reg (EU) 2016/425 on personal protective equipment.
- Comply with the applicable standard EN 149:2001+A1:2009.

EN 149:2001+A1:2009					
TEST	FFP 2 REQUIRED LEVEL	LABORATORY	REPORT N° & DATE	RESULTS	
Oil paraffin penetration	< 6 % after 120mg exposure	exposure			
NaCl penetration	< 6 % after 120mg exposure		No 1.24.11.21 12/11/2024	Compliant	
Total inward leakage	≤ 11 % for at least 46 results over 50 ≤ 8 % for at least 8 arithmetic average over 10				
Air permeability inhalation 30 l/min	≤ 0,7 mbar	Inspec International BV (2849)			
Air permeability inhalation 95 l/min	≤ 2,4 mbar				
Air permeability exhalation 160 l/min	≤ 3 mbar				
Carbon dioxide content	< 1,0 %				
Flammability	Must not burn or continue to burn for more than 5 seconds after the withdrawal of the flame				
Annual surveillance according to module D - Reg (EU) 2016/425 done by BSI (2797)					

LOGISTICS

Item	FFP	Mask qty per	Box	Poids	Boxes qty	Case	Poids
	Class	box	size	boite	per case	size	carton
M62110V	2	12	245 x 95 x 240 mm	310 g	12	508 x 305 x 498 mm	4,60 kg

EAN codes

Item	Outer case	Вох	
M62110V	3 662 036 023 773	3 662 036 023 780	

