

## M62110 FFP2 NR respiratory protective mask – without valve

Category III Personal Protective Equipment

### FEATURES & BENEFITS

- Folded 3-panel design adapts to various face shapes and sizes.
- Sealing foams on both the upper and lower panels ensure a perfect seal while providing unmatched comfort for the wearer.
- Easy to put on and adjust thanks to sliding elastic straps and a tightening ring.
- Its individual packaging helps control the risk of contamination.

### Recommended uses

- Protection against viruses and bacteria
- Hospital services, in particular to protect healthcare staff in infectious disease units
- Environments with moderate level of fine dust (construction, drilling/sanding, agriculture)
- Pharmaceutical industry and laboratories
- Work in moderately hazardous environments (metallurgy, woodworking, textiles).



### PRODUCT DETAILS

|                |  |
|----------------|--|
| Product name : | <b>SafeMask® Fit+Pro</b>                     |
| Product type : | Single use, non sterile                      |
| Fasteners:     | Sliding transverse elastics                  |
| Composition :  | Nose strip: Aluminium                        |
|                | Foams: PVC                                   |
|                | Elastics: Spandex + polyester                |
|                | Inner & outer layers: Spunbond polypropylene |
|                | Filter: Meltblown polypropylene              |
| Origin :       | China  |

| Item   | FFP Class | Valve Yes/no | Elastic Color | Unit weight (+/- 10%) | Qty / box |
|--------|-----------|--------------|---------------|-----------------------|-----------|
| M62110 | FFP2 NR   | No           | Blue          | 13,8 g                | 20        |

### CERTIFICATIONS & STANDARDS

- In accordance with requirements of Reg (EU) 2016/425 on personal protective equipment.
- Comply with the applicable standard EN 149:2001+A1:2009.

| EN 149:2001+A1:2009  |   |                                   |                             |           |
|--|---|-----------------------------------|-----------------------------|-----------|
| TEST   | FFP 2<br>REQUIRED LEVEL   | LABORATORY                        | REPORT N°<br>& DATE         | RESULTS   |
| Oil paraffin penetration   | < 6 % after 120mg exposure  | Inspec International BV<br>(2849) | No 1.24.11.21<br>12/11/2024 | Compliant |
| NaCl penetration   | < 6 % after 120mg exposure  |                                   |                             |           |
| Total inward leakage   | ≤ 11 % for at least 46 results over 50<br>≤ 8 % for at least 8 arithmetic average over 10         |                                   |                             |           |
| Air permeability<br>inhalation 30 l/min  | ≤ 0,7 mbar  |                                   |                             |           |
| Air permeability<br>inhalation 95 l/min  | ≤ 2,4 mbar  |                                   |                             |           |
| Air permeability<br>exhalation 160 l/min   | ≤ 3 mbar  |                                   |                             |           |
| Carbon dioxide content   | < 1,0 %   |                                   |                             |           |
| Flammability   | Must not burn or continue to burn for more<br>than 5 seconds after the withdrawal of the<br>flame |                                   |                             |           |
| Annual surveillance according to module D - Reg (EU) 2016/425 done by BSI (2797) |   |                                   |                             |           |

### LOGISTICS

| Item   | FFP<br>Class | Mask qty per<br>box | Box<br>size          | Box<br>weight | Boxes qty<br>per case | Case<br>size          | Case<br>weight |
|--------|--------------|---------------------|----------------------|---------------|-----------------------|-----------------------|----------------|
| M62110 | 2            | 20                  | 245 x 95 x 240<br>mm | 380<br>g      | 12                    | 508 x 305 x 498<br>mm | 5,50<br>kg     |

### EAN codes

| Item   | Outer case        | Box               |
|--------|-------------------|-------------------|
| M62110 | 3 662 036 023 810 | 3 662 036 023 827 |