

SafeMask®

Fit+Pro

Technical Data Sheet

M63110

FFP3 NR respiratory protective mask – without valve

Category III Personal Protective Equipment

FEATURES & BENEFITS

- Folded 3-panel design adapts to various face shapes and sizes.
- Sealing foams on both the upper and lower panels ensure a perfect seal while providing unmatched comfort for the wearer.
- Easy to put on and adjust thanks to sliding elastic straps and a tightening ring.
- Its individual packaging helps control the risk of contamination.

Recommended uses

- Protection against toxic aerosols and high level of fine dust (asbestos)
- Environments with high concentrations of pollutants
- Hospital services, in particular to protect healthcare staff in infectious disease units
- Work in hazardous industrial environments (chemistry, welding, grinding)
- Hospitals and high-security laboratories (handling highly contagious pathogens)
- Work in areas with a risk of exposure to highly transmissible diseases especially during pandemic



PRODUCT DETAILS

Product name :	SafeMask® Fit+Pro
Product type :	Single use, non sterile
Fasteners:	Sliding transverse elastics
Composition :	Nose strip: Aluminum
	Foams: PVC
	Elastics: Spandex + polyester
	Inner & outer layers: Spunbond polypropylene
	Filter: Meltblown polypropylene
Origin :	China

Item	FFP Class	Valve Yes/no	Elastic Color	Unit weight (+/- 10%)	Qty / box
M63110	FFP3 NR	No	Red	14,7 g	20

CERTIFICATIONS & STANDARDS

- In accordance with requirements of Reg (EU) 2016/425 on personal protective equipment.
- Comply with the applicable standard EN 149:2001+A1:2009.

EN 149:2001+A1:2009				
TEST	FFP3 REQUIRED LEVEL	LABORATORY	REPORT N° & DATE	RESULTS
Oil paraffin penetration	< 1 % after 120mg exposure	Inspec International BV (2849)	No 1.24.11.21 12/11/2024	Compliant
NaCl penetration	< 1 % after 120mg exposure			
Total inward leakage	≤ 5 % for at least 46 results over 50 ≤ 2 % for at least 8 arithmetic average over 10			
Air permeability inhalation 30 l/min	≤ 1 mbar			
Air permeability inhalation 95 l/min	≤ 3 mbar			
Air permeability exhalation 160 l/min	≤ 3 mbar			
Carbon dioxide content	< 1,0 %			
Flammability	Must not burn or continue to burn for more than 5 seconds after the withdrawal of the flame			
Annual surveillance according to module D - Reg (EU) 2016/425 done by BSI (2797)				

LOGISTICS

Item	FFP Class	Mask qty per box	Box size	Box weight	Boxes qty per case	Case size	Case weight
M63110	3	20	245 x 95 x 240 mm	420 g	12	508 x 305 x 498 mm	5,55 kg

EAN Codes

Article	Carton	Boîte
M63110	3 662 036 023 834	3 662 036 023 841