

DATA SHEET WEECOVER

REF : WL-C-0X



FEATURES: Coverall with hood. Elasticated hood, waist, and ankles
Knitted cuff
Self-adhesive zip flap

FABRICS AND SEAMS: White SMS 55 ^{GM2} – Serged seams 4 threads

PHYSICAL PERFORMANCE

Fabric Physical Properties	Test Method	Class
Abrasion resistance	EN530	Class 2
Flex cracking	ISO 7854 B	Class 3
Trapezoidal Tear	ISO 9073-4	Class 2
Tensile strength	ISO 13934-1	Class 2
Puncture resistance	EN863	Class 2

FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530

Fabric Chemical Properties	Penetration	Repellency
Sulphuric Acid 30%	Class 2	Class 3
Sodium Hydroxide 10%	Class 3	Class 3

WHOLE SUIT TEST PERFORMANCE

Dry particles Type 5 Method as defined by EN ISO 13982-1:2004 + A1:2010	Pass
Light splashes Type 6 Method as defined by EN 13034 : 2005 +A1: 2009	Pass
Protection factor according to EN 1073-2:2002	Class 1
Surface resistivity EN 1149-5	Pass
Seam Strength ISO 13935-2	Class 3

CHART SIZE

Size	WeeSafe reference	Body Height	Chest
M	WL-C-02	170-176 cm	92-100 cm
L	WL-C-03	176-182 cm	100-108 cm
XL	WL-C-04	182-188 cm	108-116 cm
XXL	WL-C-05	188-194 cm	116-124 cm
XXXL	WL-C-06	192-200 cm	124-132 cm

PACKAGING

	Units	Weight	Size	Volume
Carton	50	11 KG	45 X 28 X 68 CM	0,0857 ^{M3}
Pallet	650	145 KG	80 X 120 CM	1.714 ^{M3}

GENCOD

CARTON	M	3701012800035	L	3701012800059	XL	3701012800073	XXL	3701012800097	XXXL	3701012800110
POLYBAG		3701012800028		3701012800042		3701012800066		3701012800080		3701012800103

CUSTOM CODE : 6210109800

WeeSafe – IMMEUBLE "LE FUJY"- 1 RUE DU CENTRE 93160 NOISY-LE-GRAND - FRANCE – Tél : + 33 (0)1 43 09 98 04
Courriel : contact@weesafe.fr

